# 1M, 2M, 5M, 8M & 10M INFLATABLE AIR TRACKS

Our air tracks are perfect for casualty recovery, temporary pontoon, rescue platform or access path. It offers clearance on ice, mud flats and unstable terrain.

Available in various sizes, from 1m to 10m in length. For increased capacity several inflatable paths can be connected together. Connected lengthways to extend the path, or sideways to create a rescue raft.

This inflatable is compact and portable, packing away neatly into a storage bag (supplied). It can be inflated and deployed quickly allowing rescue personnel to react within minutes.

#### Features

- Non-slip top surface
- Strong, durable and stable
- Drop stitch construction
- 8cm floor thickness
- Max pressure 0.7bar / 10psi
- Inflation & relief valves fitted
- Versatile and low maintenance
- Guide lines available fitted on
- D-rings running parallel - 5 colours available

### Whats Supplied With The Inflatable?

- 1 (or) 2 Inflation Valve Fittings
- 1x HP2 Inflation Hand Pump
- 1x Storage Bag
- 1x Repair Kit & Tools

#### Inlet & relief valves



Soft grip handles



### **DESCRIPTION**

**INFLATABLE EQUIPMENT** 

## STOCK CODE

INFLATABLE-AIR-TRACK-'LENGTH'

NORTHERN DIVER +44 (0) 1257 25 44 44 | INFO@NDIVER.COM VISIT WWW.NDIVER-RESCUE.COM Why not design your own? We can create bespoke inflatables please contact us to discuss your requirements.



**BAY SAR DEMO DAY** 



Can be supplied with cylinder for inflation. Contact us to enquire.

# 1M, 2M, 5M, 8M & 10M **INFLATABLE AIR TRACKS**



Spec Details	10m Air Track	8m Air Track	5m Air Track	2m Air Track	1m Air Track
Overall length	1000cm	800cm	500cm	200cm	100cm
Overall width	140cm	140cm	140cm	100cm	100cm
Internal width	n/a	n/a	n/a	n/a	n/a
Sponson/pontoon dia.	n/a	n/a	n/a	n/a	n/a
Floor materials	DWF	DWF	DWF	DWF	DWF
Floor thickness	8cm	8cm	8cm	8cm	8cm
Weight	38kg	32.5kg	25kg	8kg	3kg
Carton/packing dims.	140*35*38cm	140*35*35cm	140*35*30cm	105*35*15cm	110*35*10cm
Chambers	1	1	1	1	1
Max inlet fill	0.7bar/10psi	0.7bar/10psi	0.7bar/10psi	0.7bar/10psi	0.7bar/10psi
SS316 stainless steel D-rings	28+	25+	20+	4+	4+
Handles	4	4	4	2	2
Max loading	840kg	672kg	420kg	120kg	60kg
Max persons	8+1	6+1	4	1	1





Storage Bag

Repair Kit/Tools

